



Re-Roof Information Sheet Residential



City of Redding
777 Cypress Avenue
Redding CA 96001
Tel.: (530) 225-4013
FAX: (530) 225-4360
www.ci.redding.ca.us

Project Address: _____

Slope of Roof _____ # Existing Layers _____ Existing Roofing Material _____

Check all that apply for the new roof:

<input type="checkbox"/> composition	<input type="checkbox"/> tile	<input type="checkbox"/> shake	<input type="checkbox"/> wood shingle
<input type="checkbox"/> built-up	<input type="checkbox"/> bitumen	<input type="checkbox"/> metal	<input type="checkbox"/> other _____

<input type="checkbox"/> tear off existing	<input type="checkbox"/> overlay	<input type="checkbox"/> new sheathing
--	----------------------------------	--

Is the building in the High Fire Hazard Severity Zone? Yes No

What is the Fire Class of the Proposed Roofing Material? Class A Class B Class C
(map of the zone can be seen at: <http://www.ci.redding.ca.us/devserv/pdfs/fire/fire-hazard-zone.pdf>)

Fill out **BOTH** forms for **all re-roofs**: *CF-1R-ALT-Reroof* and *CF-6R-ENV-01*

-----**INSTRUCTIONS FOR RESIDENTIAL PROJECTS**-----

- **Fill out *CF-1R-ALT-Reroof* and *CF-6R-ENV-01* forms for all re-roofs.**
- Re-roofing projects in the High Fire Hazard Severity Zone must be Class A rated. For all roofing materials other than composition shingles, a specification sheet from the roofing manufacturer must accompany this application showing compliance with required Class A rating.
- No plastic, fiberglass, or acrylic roofing panels may be used unless installed per CBC section 2609. This includes residential patio covers.
- Inspections are required for **pre re-roof** (after existing roof is removed or prior to installing overlay), **roof nail** (for roofs with new sheathing), and **final**.
- Tile Roofing: Tile may only be used to replace an existing tile roof. Exceptions:
 - Lightweight tile of 6 p.s.f. or less is installed when replacing wood shake/shingle or composition roof.
 - Prior approval received by showing that existing roof structure is adequate to support additional loads.
- Roof overlays are allowed when installed per CBC section 1510. New roof applications of any type cannot cover shake, clay, cement or asbestos tiles and cannot cover more than one existing roof application.
- All repairs resulting in exposed rafter tails, fascia boards and roof sheathing exposed to the weather are required to be painted prior to final approval of permit.
- All roof mounted HVAC units shall be securely bolted to roof framing with condensate lines secured and run to rain gutters or edge of roof.
- Per CBC section 1510, "Existing vent flashing, metal edging, drain outlets, collars and metal counterflashings shall not be reinstalled where rusted, damaged or deteriorated." Sheet metal may be reinstalled only when there is light surface rust if it is wire brushed and repainted with rust prohibiting outdoor paint.

Applicant Signature _____ Date _____